

SPRAY SHIELDS

Pipeline Equipment



Metal Safety Spray Shields for flanges & valves, prevent hazardous leaks & sprays.

Manufactured from 316 stainless steel metal bands designed to fit around a flanged connection to control a hazardous leak or spray-out.

Designed to protect personnel, equipment, and the environment, shields are used in applications of high temperatures, high pressure, or when conditions are unfavourable for cloth Safety Spray Shields.

Metal Shields have a construction that contains special metal netting inside of the band that safely dissipates pressurized sprays by distributing it around the flange circumference.

These shields contain no sharp edges, require no tools to install, easy and quickly fitted via the adjustable quick fastening clamp.

Our Metal Shields are reusable and available for all size flanges, including oval and square flanges.

- Complete visibility of studs & nuts
- No sharp edges
- Minimal Space requirements
- Available in widths of 2" & 2-3/4"
- Maximum operation temperature 1093°C (2000°F)
- Suitable for hazardous processes of high temperature, high pressures, steam, chemicals and flammables for fire prevention.

Ordering Information:

Standard width is 50mm (2")

Order by Flange ID & Pressure Rating

Or contact your local office for sizes available

All written data and statements herein are provided in good faith and believed to be reliable and appropriate at the time of drafting this document. However it is given without implied or express guarantee. Potential uses are urged to trial and /or conduct conformity test of the product to deem its suitable in application for a particular end use prior to purchase.

<p>Vic/Tas/SA 03 9764 2651 melbourne@savcor.com.au</p>	<p>NSW 02 9807 4542 sydney@savcor.com.au</p>	<p>QLD/NT 07 5549 2248 brisbane@savcor.com.au</p>	<p>WA 08 6240 3900 perth@savcor.com.au</p>
--	--	---	--